

測点番号	C002				
標準海水	K ₁₅ =		BATCH=		
検定日	3/2	検定時刻	1735	室温	24
測定者	長江、田嶋、鈴木、宮本				

ポトル	STD/SUB	3	7	11	15	19	23	
恒溫槽 水温		27.5870	27.5870	27.5870	27.5870		27.5870	
伝導比		1.94988 4981 4983 4982	1.97522 24 25	1.98611 10 11	1.98594 95 94	1.98586 86 86	1.98631 29 31	
平均		1.94982	1.97524	1.98611	1.98594	1.98586	1.98630	
備考								
ポトル	STD/SUB	4	8	12	16	20	24	
恒溫槽 水温	27.5871	27.5870	27.5870	27.5870	27.5870	27.5870	27.5870	
伝導比	1.97749 47 49	1.95108 5106 5106	1.97962 60 61	1.98628 28 30	1.98591 90 93	1.98589 87 89	1.98636 36 48 48 46	
平均	1.97748	1.95107	1.97961	1.98629	1.98591	1.98588	1.98647	
備考								
ポトル		1	5	9	13	17	21	25
恒溫槽 水温		27.5871	27.5870	27.5870	27.5870	27.5870	27.5870	27.5870
伝導比		1.95987 87 86	1.95834 5835 5835	1.98279 8281 8281	1.98606 05 07	1.98587 87 88	1.98587 88 88	1.98792 86 99 00 96
平均		1.95987	1.95835	1.98280	1.98606	1.98587	1.98588	1.98798
備考								
ポトル		2	6	10	14	18	22	26
恒溫槽 水温		27.5871	27.5870	27.5870	27.5870	27.5870	27.5870	27.5870
伝導比		1.95458 61 62 61	1.97044 7041 7041	1.98574 76 75	1.98595 97 98	1.98586 86 86	1.98616 8616 8616	1.98688 85 85
平均		1.95461	1.97042	1.98575	1.98597	1.98586	1.98616	1.98686
備考								