

KS-14-7

## SALINITY DETERMINATION

No. 4

測点番号	C016						
標準海水	K <sub>15</sub> =		BATCH=				
検定日	5/24	検定時刻	13:38	室温	24.1℃		
測定者	林, 中田						

ボトル	STD/SUB	3	7	11	15	19	23	
恒溫槽 水温	29.5853							
伝導比	1.98446 46 47	1.98430 30 29	1.98336 37 35	1.98060 60 60	1.96993 93 93	1.97875 74 73	1.99092 91 90	
平均	1.98446	1.98430	1.98336	1.98060	1.96993	1.97874	1.99091	
備考								
ボトル	STD/SUB	4	8	12	16	20	24	
恒溫槽 水温								
伝導比		1.98420 19 20	1.98271 71 71	1.97931 31 32	1.96136 36 37	1.98565 64 64	1.99085 84 84	
平均		1.98420	1.98271	1.97931	1.96136	1.98564	1.99084	
備考								
ボトル	STD/SUB	1	5	9	13	17	21	25
恒溫槽 水温								
伝導比	1.98441 40 41	1.98401 00 01	1.98225 25 23	1.97723 23 21	1.94961 61 59	1.98617 16 17	1.99121 21 21	
平均	1.98441	1.98401	1.98224	1.97723	1.94960	1.98617	1.99121	
備考								
ボトル	STD/SUB	2	6	10	14	18	22	26
恒溫槽 水温								
伝導比	1.98439 39 38	1.98376 77 77	1.98163 63 64	1.97428 29 28	1.96059 58 59	1.98742 42 41	1.99112 09 11 11 12	
平均	1.98439	1.98377	1.98163	1.97428	1.96058	1.98742	1.99111	
備考								