

測点番号	C001				
標準海水	K <sub>15</sub> =0.99981 BATCH= P155 1.99962				
検定日	5/21	検定時刻	10:05	室温	29.8℃
測定者	柳本,伊藤,山本,富本,中田				恒温槽 25℃ に設定

ボトル	STD/SUB	3	7	11	15	19	23	
恒温槽 水温	27.5915	27.5910	27.5909	27.5910	27.5909	27.5907	27.5908	
伝導比	1.99962 62 61	1.98419 20 20	1.98272 72 73	1.97944 44 44	1.96180 81 80	1.97596 95 97	1.99466 65 66	
平均	1.99962	1.98420	1.98272	1.97944	1.96180	1.97596	1.99466	
備考								
ボトル	STD/SUB	4	8	12	16	20	24	
恒温槽 水温	27.5911	27.5910	27.5908	27.5910	27.5909	27.5908	27.5908	
伝導比	1.98844 45 44	1.98403 03 03	1.98222 (19 18 17)	1.97973 72 73	1.95559 58 59	1.98565 66 66	1.99502 01 01	
平均	1.98844	1.98403	1.98218	1.97973	1.95559	1.98566	1.99501	
備考								
ボトル	1	5	9	13	17	21	25	
恒温槽 水温	27.5911	27.5910	27.5909	27.5910	27.5908	27.5908	27.5909	
伝導比	1.98444 46 45	1.98375 74 76	1.98163 62 62	1.97440 40 38	1.94915 1.94913 14	1.98799 78 98	1.99544 44 46	
平均	1.98445	1.98375	1.98162	1.97439	1.94914	1.98798	1.99545	
備考								
ボトル	2	6	10	14	18	22	26	
恒温槽 水温	27.5910	27.5908	27.5909	27.5910	27.5907	27.5908	27.5909	
伝導比	1.98436 1.98436 1.98437	1.98333 33 31	1.98079 78 78	1.96996 (91 92 91)	1.96195 93 94	1.99253 52 52	1.99539 41 42	
平均	1.98436	1.98332	1.98078	1.96991	1.96194	1.99252	1.99541	
備考								