

KS-15-14

SALINITY DETERMINATION

No. /

| 測点番号 | C002 | | | | | | | |
|-----------|--------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------------------|
| 標準海水 | $K_{15} = 0.99970$ BATCH= P158 | | | | | | | |
| 検定日 | 2015/11/19 | 検定時刻 | 17:15- | 室温 | 24.5°C | | | |
| 測定者 | 木村、吉本 | | | | | | | |
| ボトル | STD/SUB | 3 | 7 | 11 | 15 | 19 | 23 | SUB |
| 恒温槽 水温 | | 24.5965 | 24.5965 | 24.5965 | 24.5965 | 24.5965 | 24.5965 | 24.5965 |
| 伝導比 | 0.99970 1.99940 | 1.98434 32 33 | 1.98378 77 | 1.98164 65 63 | 1.96306 06 | 1.98275 75 75 | 1.98059 59 59 | 1.98284 |
| 平均 | 1.99940 | 1.98433 | 1.98377 | 1.98164 | 1.96306 | 1.98275 | 1.98059 | |
| 備考 | Batch: P158 | | | | | | | |
| ボトル | STD/SUB | 4 | 8 | 12 | 16 | 20 | 24 | SUB |
| 恒温槽 水温 | | | | 24.5965 | | | 24.5965 | 24.5965 |
| 伝導比 | 1.98279 79 80 | | | 1.97931 31 32 | | | 1.98059 58 57 | 1.98279 79 81 |
| 平均 | 1.98279 | | | 1.97931 | | | 1.98058 | 1.98280 |
| 備考 | | | | | | | | |
| ボトル | 1 | 5 | 9 | 13 | 17 | 21 | 25 | STD |
| 恒温槽 水温 | | 24.5965 | 24.5965 | 24.5966 | 24.5965 | 24.5965 | 24.5965 | |
| 伝導比 | 1.98499 98 48 | 1.98420 21 22 | 1.98345 44 | 1.97402 02 01 | 1.95299 99 | 1.99052 51 52 | 1.98102 02 02 | 1.99936 37 39 38 38 |
| 平均 | 1.98448 | 1.98421 | 1.98344 | 1.97402 | 1.95299 | 1.99052 | 1.98102 | 1.99938 |
| 備考 | | | | | | | | |
| ボトル | 2 | 6 | 10 | 14 | 18 | 22 | 26 | |
| 恒温槽 水温 | 24.5965 | 24.5965 | 24.5965 | 24.5965 | 24.5965 | 24.5965 | 24.5965 | |
| 伝導比 | 1.98442 42 41 | 1.98407 07 08 | 1.98277 81 79 | 1.96953 54 53 | 1.96535 36 35 | 1.98788 87 89 | 1.97722 21 21 | |
| 平均 | 1.98442 | 1.98407 | 1.98279 | 1.96953 | 1.96535 | 1.98788 | 1.97721 | |
| 備考 | | | | | | | | |