

KS-14-7

SALINITY DETERMINATION

No. 5

測点番号	C 617				
標準海水	K ₁₅ =		BATCH=		
検定日	5/24	検定時刻	15:09	室温	22.8℃
測定者	中田、多田、鈴木、柳本				

ボトル	STD/SUB	3	7	11	15	19	23	SUR
恒溫槽 水温	27.5855	27.5853	27.5852	27.5855	27.5854	27.5853	27.5856	27.5855
伝導比	1.98448 49 48	1.98435 35 34	1.98334 35 35	1.98085 86 85	1.96956 57 57	1.97898 99 98	1.98793 92 91	1.98448 49 X52 50
平均	1.98448	1.98435	1.98335	1.98085	1.96957	1.97898	1.98792	1.98449
備考								
ボトル	STD/SUB	4	8	12	16	20	24	STD
恒溫槽 水温		27.5853	27.5853	27.5855	27.5853	27.5854	27.5857	27.5858
伝導比		1.98422 22 22	1.98281 83 83	1.97938 38 37	1.96201 62 62	1.98530 28 28	1.98799 95 98	1.99958 60 60 60
平均		1.98422	1.98282	1.97938	1.96202	1.98529	1.98799	1.99960
備考								
ボトル	1	5	9	13	17	21	25	
恒溫槽 水温	27.5855	27.5852	27.5854	27.5855	27.5853	27.5855	27.5856	
伝導比	1.98447 47 48	1.98403 03 03	1.98242 41 42	1.97722 23 21	1.95163 62 62	1.98498 96 97	1.98832 32 32	
平均	1.98447	1.98403	1.98242	1.97722	1.95162	1.98497	1.98832	
備考								
ボトル	2	6	10	14	18	22	26	
恒溫槽 水温	27.5854	27.5852	27.5855	27.5854	27.5852	27.5856	27.5856	
伝導比	1.98445 45 44	1.98376 77 74	1.98175 75 75	1.97721 19 21	1.95889 90 90	1.98862 61 62	1.98859 57 56	
平均	1.98445	1.98376	1.98175	1.97720	1.95890	1.98862	1.98856	
備考								