

|      |                   |      |        |    |       |
|------|-------------------|------|--------|----|-------|
| 測点番号 | C009              |      |        |    |       |
| 標準海水 | K <sub>15</sub> = |      | BATCH= |    |       |
| 検定日  | 5/22              | 検定時刻 | 04:05~ | 室温 | 24.3℃ |
| 測定者  | 宮本 山口 中田 772      |      |        |    |       |

| ボトル       | STD/SUB             | 3                   | 7                   | 11                   | 15                  | 19                               | 23                        | SUB                 |
|-----------|---------------------|---------------------|---------------------|----------------------|---------------------|----------------------------------|---------------------------|---------------------|
| 恒溫槽<br>水温 | 27.5884             | 27.5885             | 27.5884             | 27.5885              | 27.5884             | 27.5884                          | 27.5884                   | 27.5884             |
| 伝導比       | 1.98458<br>56<br>57 | 1.98437<br>39<br>39 | 1.98337<br>37<br>38 | 1.98083<br>83<br>82  | 1.96893<br>92<br>92 | 1.98119<br>20<br>18              | 1.98958<br>59<br>59       | 1.98459<br>59<br>60 |
| 平均        | 1.98457             | 1.98438             | 1.98337             | 1.98083              | 1.96892             | 1.98119                          | 1.98959                   | 1.98459             |
| 備考        |                     |                     |                     |                      |                     |                                  |                           | 1.98459             |
| ボトル       | STD/SUB             | 4                   | 8                   | 12                   | 16                  | 20                               | 24                        |                     |
| 恒溫槽<br>水温 |                     | 27.5884             | 27.5884             | 27.5884              | 27.5885             | 27.5885                          | 27.5884                   |                     |
| 伝導比       |                     | 1.98428<br>30<br>30 | 1.98278<br>79<br>79 | 1.97929<br>728<br>28 | 1.96079<br>80<br>81 | 1.98500<br>498<br>498<br>1.98499 | 1.99013<br>13<br>12       |                     |
| 平均        |                     | 1.98429             | 1.98279             | 1.97928              | 1.96080             | 1.98499                          | 1.99013                   |                     |
| 備考        |                     |                     |                     |                      |                     | 110決に101<br>定, 1.98455           |                           |                     |
| ボトル       | 1                   | 5                   | 9                   | 13                   | 17                  | 21                               | 25                        |                     |
| 恒溫槽<br>水温 | 27.5884             | 27.5884             | 27.5884             | 27.5884              | 27.5884             | 27.5884                          | 27.5884                   |                     |
| 伝導比       | 1.98453<br>54<br>54 | 1.98410<br>09<br>11 | 1.98227<br>27<br>28 | 1.97919<br>18<br>18  | 1.95098<br>98<br>96 | 1.98804<br>06<br>04              | 1.99349<br>50<br>51       |                     |
| 平均        | 1.98454             | 1.98410             | 1.98227             | 1.97918              | 1.95097             | 1.98805                          | 1.99350                   |                     |
| 備考        |                     |                     |                     |                      |                     |                                  |                           |                     |
| ボトル       | 2                   | 6                   | 10                  | 14                   | 18                  | 22                               | 26                        |                     |
| 恒溫槽<br>水温 | 27.5885             | 27.5884             | 27.5884             | 27.5883              | 27.5884             | 27.5884                          | 27.5884                   |                     |
| 伝導比       | 1.98451<br>51<br>53 | 1.98379<br>81<br>80 | 1.98172<br>71<br>70 | 1.97420<br>21<br>21  | 1.95991<br>91<br>93 | 1.98984<br>85<br>86              | 1.99338<br>35<br>36<br>35 |                     |
| 平均        | 1.98452             | 1.98380             | 1.98171             | 1.97421              | 1.95992             | 1.98985                          | 1.99335                   |                     |
| 備考        |                     |                     |                     |                      |                     |                                  |                           |                     |